

MEMS and Photonics Module Integration Into Sige Bicmos Technologies for More Than Moore Functional Diversification

To cite this article: Bernd Tillack *et al* 2013 *Meet. Abstr.* **MA2013-02** 2221

View the [article online](#) for updates and enhancements.

You may also like

- [Requirements and Difficult Challenges for Packaging in the Era of "More Than Moore"](#)
Wilmer R Bottoms
- [Inemi and Its Collaborative Approach and Preliminary Plan for Addressing More Than Moore Roadmapping](#)
Charles Edward Richardson
- [Technology Roadmapping of ICs "More than Moore" Functional Diversification](#)
Bill Bader and Michael Gaitan



Your Lab in a Box!

The PAT-Tester-i-16: All you need for Battery Material Testing.

- ✓ All-in-One Solution with integrated Temperature Chamber!
- ✓ Cableless Connection for Battery Test Cells!
- ✓ Fully featured Multichannel Potentiostat / Galvanostat / EIS!

www.el-cell.com +49 40 79012-734 sales@el-cell.com

EL-CELL[®]
electrochemical test equipment



MEMS and Photonics Module Integration into SiGe BiCMOS Technologies for More than Moore Functional Diversification

B. Tillack^{1,2}, B. Heinemann¹, M. Kaynak¹, D. Knoll¹, A. Mai¹, H. Rücker¹, Y. Yamamoto¹, and L. Zimmermann¹

¹IHP, Im Technologiepark 25,15236 Frankfurt (Oder), Germany,

²Technische Universität Berlin, HFT4, Einsteinufer 25, 10587, Berlin, Germany

“More Than Moore” functional diversification by combining different technologies is enlarging the spectrum for embedded system applications. In this paper we focus on the monolithic integration approach of optical components into the front-end-off-line (FEOL) to combine electronics and photonics (Si Photonics), and of MEMS (micro-electro-mechanical systems) into the back-end-off-line (BEOL) of SiGe BiCMOS technologies.

The SiGe BiCMOS baseline process combines high-speed SiGe HBTs and computing power of CMOS on a single chip with HBTs reaching up to 300/500 GHz f_T/f_{max} and 2.0 ps CML gate delay [1, 2]. The half THz HBTs are available within the 0.13 μm BiCMOS technology SG13G2 of IHP [3] making operating frequencies from 100 GHz up to several hundred GHz accessible for monolithically integrated millimeter-wave systems for high-speed wireless and fiber-optics communications, mm-wave imaging, and radar systems [e.g. 4-7].

Many present developments focus on integrated photonics technologies, in particular on the convergence of silicon IC technology and integrated optics (silicon photonics). A main advantage of using an ultrafast SiGe BiCMOS technology for the integration of optical components is its capability for high speed multilevel optical communication e.g. trans impedance amplifier (TIA) for optical receivers, modulator drivers with high voltage swing, laser drivers, multilevel high-speed drivers for optical modulators. As an example for the fabrication of photonics components, a cross section of a Ge photodiode is shown in Fig. 1. The photodiode was fabricated in a BiCMOS compatible process flow. Photodiodes with very low dark current have been shown [8].

Several concepts have been suggested to integrate MEMS components into semiconductor processes using hybrid and monolithic approaches. The key advantage of the monolithic integration is the potentially lower interconnect loss compared to hybrid integration concepts. Whereas the interconnect loss for hybrid or heterogeneously integrated systems is acceptable for frequencies below 40 GHz, it becomes much more important for frequencies above 60 GHz, limiting the overall system performance. Fully embedded solutions at higher mm-wave frequencies become attractive for applications, such as 60 GHz personal area networks, automotive radars in the 76-81 GHz range, or security radar/imaging at 94 and 140 GHz. Moreover, multi-band/wide-band operation and phased-array antennas for next generation high-frequency systems would be feasible by integrating MEMS modules into SiGe BiCMOS technology. As an example, measured and simulated S parameter results are shown in Fig. 2 for a RF switch integrated in the BEOL of the SiGe BiCMOS process. The insertion loss of the switch in the 1-110 GHz frequency range is below 1.65 dB. The isolation for frequencies between 60 GHz and 100 GHz is better than 15 dB [9].

In summary, the paper demonstrates the successful monolithic integration of photonics and MEMS components into BiCMOS technologies with fast SiGe HBTs enabling More than Moore functional diversification for cost effective multifunctional systems.

References

[1] B. Heinemann et al., IEEE IEDM Techn. Dig., pp. 688-691, 2010.
 [2] A. Fox et al., IEEE BCTM Proc., pp. 70-73, 2011.
 [3] H. Rücker et al., IEEE SiRF Symp. Dig., pp. 129-132, 2012.
 [4] U. Pfeiffer et al., IEEE ISSCC Dig. Techn. Papers, pp. 416-417, 2010.
 [5] E. Öjefors et al., IEEE Microwave Theory Techn., vol. 60, no. 5, pp. 1397-1004, 2012.
 [6] K. Schmalz et al., IEEE RFIC Symp., June 2012.
 [7] E. Öjefors et al., IEEE ISSCC Dig. Techn. Papers, pp. 15-17, 2011.
 [8] S. Lischke, et al., IEEE Photonics Conf. 2012, pp. 628- 629, 2012.
 [9] M. Kaynak, et al., Silicon Monolithic Integrated Circuits in RF Systems (SiRF), pp.144-147, 2010.




Fig. 1: SEM cross-sections of a Ge photodiode fabricated in a BiCMOS compatible process flow [8].




Fig. 2: Measured and simulated S parameter results of the MEMS switch for both “up” and “down” states [9].